## NSN 5930-01-174-7514

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-174-7514

Body Style:
Hole mounted
Overall Length:
1.609 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.312 inches
Overall Height:
0.594 inches
Overall Width:
0.500 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.101 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.250 inches
Actuator Length:
0.250 inches
Actuator Style:
Rectangular
Actuator Height:
0.094 inches
Actuator Width:
0.297 inches
Actuator Free Position Height:
0.094 inches
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
3431-01-498-4423
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit

4.0 ounces

**Switch Release Force:** 

## **NSN 5930-01-174-7514** Sensitive Switch - Page 2 of 2



Switch Actuating Force:
8.0 ounces
Actuator Movement:
Between 0.050 pretravel inches and 0.015 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Special Features:
Switch
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0