NSN 5930-01-174-7671

Flow Switch - Page 1 of 1

Unit Of Measure:

Demilitarization:

No Fiig: A048b0



| View Online at https://aerobasegroup.com/nsn/5930-01-174-7671 |
|--|
| Operating Tempurature Rating: |
| Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit |
| Mounting Method: |
| Threaded bushing and line |
| Thready Qty Per Inch (tpi): |
| 14 single threaded bushing |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.500 inches single threaded bushing |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, double make, momentary action |
| Terminal Type: |
| Wire lead |
| Contact Load Current Rating: |
| 500.0 milliamperes resistive load second voltage |
| Contact Adjustability: |
| Actuation point not adjustable |
| Contact Stimulus Rating: |
| 28.00 actuation point gallons per minute |
| Contact Voltage Rating In Volts: |
| 32.0 dc at sea level second voltage |
| Frequency In Hertz: |
| 60.0 first voltage |
| Media For Which Designed: |
| Liquid |
| Thread Series Designator: |
| Npt single threaded bushing |
| Shelf Life: |
| N/a |