

View Online at <https://aerobasegroup.com/nsn/5930-01-174-8593>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Salt spray resistant and fungus resistant

Overall Length:

3.219 inches

Overall Height:

5.750 inches

Overall Width:

2.370 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 30.0 degrees fahrenheit and 110.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

7000.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, permanent jumper, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

7.5 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+1500.00 actuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point screw

Contact Stimulus Rating:

320.00 actuation point pounds per square inch gage and 245.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

600.0 ac at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas, liquefied

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0