## NSN 5930-01-175-4643



Pressure Switch - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5930-01-175-4643	
Inside Diameter:	
0.125 inches single connection	
Hazardous Locations/environmental Protection:	
Vibration proof	
Overall Length:	
5.438 inches	
Overall Height:	
5.750 inches	
Overall Width:	
3.000 inches	
Body Length:	
4.750 inches	
Pressure Switch Type:	
Differential	
Operating Tempurature Rating:	
Between -30.0 degrees fahrenheit and 110.0 degrees fahrenheit	
Mounting Method:	
Surface	
Thready Qty Per Inch (tpi):	
27 single pressure connection	
Contact Action Stimulus:	
Increase	
Proof Pressure:	
45.00 inches of water	

**Thread Size:** 

0.125 inches single pressure connection

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, both positions maintained

**Terminal Type:** 

Screw

**Contact Load Current Rating:** 

15.0 amperes resistive load single voltage

**Contact Adjustability:** 

Actuation point adjustable

**Contact Adjustment Range:** 

+3.00/+11.00 actuation point inches of water

**Contact Adjustment Type:** 

Internal actuation point screw

**Contact Voltage Rating In Volts:** 

480.0 ac at sea level single voltage

**Pressure Connector Type:** 

Plain, threaded internal single connection

## NSN 5930-01-175-4643

Pressure Switch - Page 2 of 2



Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization:

No Fiig: A048b0