# NSN 5930-01-175-7989

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-175-7989

				_			- 2		
n	е.	М	e	ı١	12	m	$\Delta$	0	r.

0.250 inches single connection

#### **Hazardous Locations/environmental Protection:**

Fungus resistant and humidity resistant and vibration resistant

**Overall Length:** 

5.000 inches

**Body Length:** 

3.690 inches

**Overall Diameter:** 

6.000 inches

**Pressure Switch Type:** 

Gage

#### **Operating Tempurature Rating:**

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

#### **Mounting Method:**

Input port

#### Thready Qty Per Inch (tpi):

18 single pressure connection

#### **Contact Action Stimulus:**

Decrease

# **Proof Pressure:**

12.00 inches per second

#### **Thread Size:**

0.250 inches single pressure connection

# **Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained

#### **Terminal Type:**

Connector, receptacle

#### **Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage

# **Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

# **Contact Stimulus Rating:**

2.10 actuation point inches per second and 2.70 deactuation point inches per second

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

# **Pressure Connector Type:**

Plain, threaded internal single connection

#### Frequency In Hertz:

60.0 first voltage

#### Media For Which Designed:

Gas

# NSN 5930-01-175-7989

Pressure Switch - Page 2 of 2



Style Designator:
Cylindrical

**Thread Series Designator:** 

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0