

View Online at <https://aerobasegroup.com/nsn/5930-01-175-8002>

**Thread Class:**

2b single mounting facility

**Overall Length:**

4.400 inches

**Overall Height:**

2.906 inches

**Overall Width:**

2.812 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.188 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section periphery

**Throw Quantity:**

7 single section periphery

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob and variable resistor

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

350.0 dc at sea level 500.0 highest ac voltage rating at sea level 125.0 lowest ac voltage rating at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes single section periphery

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

400.0 milliamperes inductive load dc at sea level  
5.0 amperes inductive load highest ac voltage rating at sea level  
20.0 amperes inductive load lowest ac voltage rating at sea level

**Precious Material And Location:**

Rotor and terminal surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0