

View Online at <https://aerobasegroup.com/nsn/5930-01-175-8002>

Thread Class:

2b single mounting facility

Overall Length:

4.400 inches

Overall Height:

2.906 inches

Overall Width:

2.812 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section periphery

Throw Quantity:

7 single section periphery

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob and variable resistor

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

350.0 dc at sea level500.0 highest ac voltage rating at sea level125.0 lowest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

400.0 milliamperes inductive load dc at sea level5.0 amperes inductive load highest ac voltage rating at sea level20.0 amperes inductive load lowest ac voltage rating at sea level

Precious Material And Location:

Rotor and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0