

View Online at <https://aerobasegroup.com/nsn/5930-01-175-8042>

Overall Length:

5.088 inches

Overall Diameter:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.221 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

7 each section rear

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

350.0 dc at sea level500.0 highest ac voltage rating at sea level125.0 lowest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

0.4 amperes inductive load dc at sea level5.0 amperes inductive load highest ac voltage rating at sea level20.0 amperes inductive load lowest ac voltage rating at sea level

Precious Material And Location:

Rotor and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, panel mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0