Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-175-8338

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.520 inches
Overall Height:
1.740 inches
Overall Width:
2.120 inches
Unthreaded Mounting Hole Diameter:
0.189 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
27192
Knob Manufacturer Part Number:
53-1160
Knob Specificationial Markings:
Man, off, auto
Longest Horizontal Distance Between Mounting Centers:
1.620 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.250 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section front
Throw Quantity:
2 single section front
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
440.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes single section front

NSN 5930-01-175-8338

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

750.0 milliamperes inductive load highest ac voltage rating at sea level

Style Designator:

Square wafer, panel mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0