NSN 5930-01-175-8343

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-175-8343

| Body Style: |
|---|
| Bushing mount |
| Overall Length: |
| 4.370 inches |
| Overall Height: |
| 1.000 inches |
| Overall Width: |
| 1.000 inches |
| Body Diameter: |
| 1.000 inches |
| Bushing Length: |
| 0.540 inches |
| Body Length: |
| 2.280 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.420 inches |
| Actuator Height: |
| 1.150 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained and center position maintained |
| Actuator Position-locking Relationship: |
| Up position no locking action and down position no locking action and center position locked in |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 2.680 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Holding solenoid |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 2 note double throw both positions maintained single switch unit |

Contact Load Current Rating At Maximum Rated Voltage: 4.000 amperes resistive dc and 2.000 amperes inductive dc

NSN 5930-01-175-8343 Toggle Switch - Page 2 of 2



| Thread Series Designator: |
|-----------------------------|
| Uns |
| Terminal Type And Quantity: |
| 8 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A053a0