NSN 5930-01-175-8347



Sensitive Switch - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5930-01-175-8347

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Case Material:
Metal
Housing Height:
1.625 inches
Housing Length:
4.547 inches

Housing Length:
4.547 inches
Housing Width:
1.844 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

Some to Some Pistance Service Troubing mounting Laborator Farance to Water.

1.156 inches

Maximum Voltage Rating In Volts:

240.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded stud

Nonpile-up Contact Arrangement:

2 two circuit, one position momentary single switch unit

Actuator Movement:

13.0 pretravel degrees and 75.0 overtravel degrees and 7.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0