## NSN 5930-01-175-8347



Sensitive Switch - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5930-01-175-8347

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Case Material:
Metal
Housing Height:
1.625 inches
Housing Length:
4.547 inches

Housing Length:
4.547 inches
Housing Width:
1.844 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

Some to Some Pistance Service Troubing mounting Laborator Farance to Water.

1.156 inches

**Maximum Voltage Rating In Volts:** 

240.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

**Mounting Method:** 

Threaded stud

**Nonpile-up Contact Arrangement:** 

2 two circuit, one position momentary single switch unit

**Actuator Movement:** 

13.0 pretravel degrees and 75.0 overtravel degrees and 7.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:** 

200.000 milliamperes resistive dc and 3.000 amperes resistive ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

8 screw

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A053a0