NSN 5930-01-175-9906

Sensitive Switch - Page 1 of 2



Body Style: Hole mounted Overall Length: 0.929 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.188 inches Overall Height: 0.610 inches Overall Width: 0.200 inches Body Length: 0.500 inches Body Width: 0.200 inches Body Height: 0.350 inches
Overall Length: 0.929 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.188 inches Overall Height: 0.610 inches Overall Width: 0.200 inches Body Length: 0.500 inches Body Width: 0.200 inches Body Height:
0.929 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.188 inches Overall Height: 0.610 inches Overall Width: 0.200 inches Body Length: 0.500 inches Body Width: 0.200 inches Body Height:
Center To Center Distance Between Mounting Facilities Parallel To Length: 0.188 inches Overall Height: 0.610 inches Overall Width: 0.200 inches Body Length: 0.500 inches Body Width: 0.200 inches Body Height:
0.188 inches Overall Height: 0.610 inches Overall Width: 0.200 inches Body Length: 0.500 inches Body Width: 0.200 inches Body Height:
Overall Height: 0.610 inches Overall Width: 0.200 inches Body Length: 0.500 inches Body Width: 0.200 inches Body Height:
0.610 inches Overall Width: 0.200 inches Body Length: 0.500 inches Body Width: 0.200 inches Body Height:
Overall Width: 0.200 inches Body Length: 0.500 inches Body Width: 0.200 inches Body Height:
0.200 inches Body Length: 0.500 inches Body Width: 0.200 inches Body Height:
Body Length: 0.500 inches Body Width: 0.200 inches Body Height:
0.500 inches Body Width: 0.200 inches Body Height:
Body Width: 0.200 inches Body Height:
0.200 inches Body Height:
Body Height:
0.350 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.849 inches
Actuator Style:
Leaf
Actuator Width:

0.090 inches

Actuator Free Position Height:

0.440 inches

Maximum Voltage Rating In Volts:

125.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

5.0 grams

Switch Actuating Force:

30.0 grams

Actuator Movement:

Between 0.115 pretravel inches and 0.025 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive ac

NSN 5930-01-175-9906 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0