## NSN 5930-01-175-9909

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-175-9909

| Body Style:   |
|---|
| Hole mounted  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.375 inches  |
| Body Length:  |
| 0.781 inches  |
| Body Width:   |
| 0.250 inches  |
| Body Height:  |
| 0.375 inches  |
| Case Material:  |
| Plastic   |
| Unthreaded Mounting Hole Diameter:  |
| 0.094 inches  |
| Actuator Length:  |
| 0.094 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.078 inches  |
| Actuator Width:   |
| 0.094 inches  |
| Actuator Free Position Height:  |
| 0.330 inches  |
| Maximum Voltage Rating In Volts:  |
| 125.0 ac  |
| Inclosure Type:   |
| Fully enclosed  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary single switch unit           |
| Contact Load Current Rating At Maximum Rated Voltage:                     |
| 0.100 amperes resistive ac  |
| Precious Material And Location:   |
| Contacts gold   |
| Terminal Type And Quantity:   |
| 3 quick disconnect, male  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## **NSN 5930-01-175-9909** Sensitive Switch - Page 2 of 2



Fiig:

A053a0