

View Online at <https://aerobasegroup.com/nsn/5930-01-176-5609>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Length:

0.560 inches

Overall Height:

1.515 inches

Overall Width:

0.560 inches

Body Diameter:

0.560 inches

Bushing Length:

0.340 inches

Body Length:

0.830 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.380 inches

Actuator Height:

0.125 inches

Actuator Free Position Height:

0.125 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

64.0 ounces

Actuator Movement:

Between 0.073 pretravel inches and 0.012 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0