

View Online at <https://aerobasegroup.com/nsn/5930-01-176-5609>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Dustproof and moisture proof

**Overall Length:**

0.560 inches

**Overall Height:**

1.515 inches

**Overall Width:**

0.560 inches

**Body Diameter:**

0.560 inches

**Bushing Length:**

0.340 inches

**Body Length:**

0.830 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.380 inches

**Actuator Height:**

0.125 inches

**Actuator Free Position Height:**

0.125 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action single switch unit

**Switch Release Force:**

16.0 ounces

**Switch Actuating Force:**

64.0 ounces

**Actuator Movement:**

Between 0.073 pretravel inches and 0.012 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0