

View Online at <https://aerobasegroup.com/nsn/5930-01-176-6474>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Dustproof and shock proof

Overall Length:

1.210 inches

Overall Height:

3.898 inches

Overall Width:

Between 0.950 inches and 0.970 inches

Body Length:

0.660 inches

Body Width:

Between 0.950 inches and 0.970 inches

Body Height:

3.688 inches

Case Material:

Metal

Actuator Length:

Between 1.020 inches and 1.050 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.164 inches and 0.210 inches

Actuator Width:

Between 0.720 inches and 0.750 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

Actuator Inscription:

Power on single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Holding solenoid and rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Special Features:

Full display lens

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 turret and 7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0