

View Online at <https://aerobasegroup.com/nsn/5930-01-176-6981>

Hazardous Locations/environmental Protection:

Corrosion resistant and salt spray resistant and vibration resistant

Overall Length:

2.368 inches

Overall Height:

1.156 inches

Body Diameter:

1.625 inches

Body Height:

0.810 inches

Unthreaded Mounting Hole Diameter:

Between 0.150 inches and 0.158 inches

Distance Between Mounting Facility Centers:

1.930 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -73.0 degrees celsius and 150.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

30.00 pounds per square inch absolute

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

4.37 actuation point pounds per square inch absolute and 4.62 actuation point pounds per square inch absolute and 4.97 deactuation point pounds per square inch absolute and 5.22 deactuation point pounds per square inch absolute

Contact Voltage Rating In Volts:

30.0 dc at altitude second voltage

Special Features:

Shock resistant

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0