NSN 5930-01-176-7216

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-176-7216

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
4.690 inches
Overall Height:
1.880 inches
Overall Width:
2.440 inches
Case Material:
Metal
Housing Height:
1.880 inches
Housing Length:
4.690 inches
Housing Width:
1.780 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.340 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.160 inches
Maximum Voltage Rating In Volts:
600.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 two circuit, one position momentary single switch unit
Switch Actuating Force:
64.0 inch-ounces
Contact Load Current Rating At Maximum Rated Voltage:
0.400 amperes resistive dc and 150.000 milliamperes inductive dc and 0.600 amperes resistive ac
Special Features:
0.750-14 npt conduit
Terminal Type And Quantity:
8 screw
Shelf Life:
N/a

NSN 5930-01-176-7216

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0