## NSN 5930-01-176-7225

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-176-7225

| Body Style:  |
|--|
| Panel mounted  |
| Overall Length:  |
| 3.234 inches   |
| Overall Height:  |
| 1.200 inches   |
| Overall Width:   |
| 0.960 inches   |
| Body Width:  |
| 0.850 inches   |
| Body Height:   |
| 1.094 inches   |
| Actuator Length:   |
| 1.040 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Height:   |
| 0.140 inches   |
| Actuator Width:  |
| 0.546 inches   |
| Actuator Color:  |
| White single actuator  |
| Illuminated Actuator Color:  |
| Green single actuator and yellow single actuator   |
| Maximum Voltage Rating In Volts:   |
| 115.0 ac and 28.0 dc   |
| Mounting Surface To Terminal End Distance:   |
| 3.094 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Nonpile-up Contact Arrangement:  |
| 2 pole, double throw, both positions maintained single switch unit   |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes         |
| inductive ac and 1.500 amperes lamp ac   |
| Test Data Document:  |
| 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

6 tab, solder lug and 6 turret

## **Specification Data:**

813/10-mil-s-22885/87 government enecification

## NSN 5930-01-176-7225

Push Switch - Page 2 of 2



| he |  |  |
|----|--|--|
|    |  |  |
|    |  |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0