NSN 5930-01-177-1169

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-177-1169
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.430 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Body Width:
1.000 inches
Body Height:
1.000 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.740 inches
Actuator Inscription:
Stop single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.160 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes
inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver and contact surfaces gold

NSN 5930-01-177-1169

Push Switch - Page 2 of 2



			_	_			
 na	h	_	Го	116	~	\sim	ο.

Unable to decode and unable to decode

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0