NSN 5930-01-177-1177

Thermostatic Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-177-1177 |
|---------------------------------------------------------------|
| Thread Class: |
| 2b all threaded hole |
| Overall Length: |
| 2.960 inches |
| Overall Height: |
| 2.362 inches |
| Overall Width: |
| 1.830 inches |
| Distance Between Mounting Facility Centers: |
| Between 1.740 inches and 1.760 inches |
| Capillary Tube Length: |
| 36.0 inches |
| Bulb Length: |
| Between 4.660 inches and 6.660 inches |
| Bulb Diameter: |
| 0.250 inches |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Mounting Method: |
| Bracket and threaded hole |
| Thready Qty Per Inch (tpi): |
| 32 all threaded hole |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.138 inches all threaded hole |
| Mounting Facility Pattern: |
| Two position in-line |
| Terminal Type: |
| Tab w/screw |
| Contact Load Current Rating: |
| 25.0 amperes resistive load single voltage |
| Contact Adjustability: |
| Actuation point adjustable |
| Contact Adjustment Range: |
| |

+86.00/+550.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point shaft

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

NSN 5930-01-177-1177

Thermostatic Switch - Page 2 of 2



| | •• | | • | _ | | |
|---|-----|----|------|--------|------|--------|
| ı | hre | ลด | Seri | 26 I I | PSIU | nator: |
| • | | uu | CCII | | COIG | mator. |

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0