NSN 5930-01-177-2329

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-177-2329

| Body Style: |
|---|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Oiltight and watertight |
| Overall Length: |
| 3.875 inches |
| Overall Height: |
| 1.547 inches |
| Overall Width: |
| 2.250 inches |
| Case Material: |
| Metal |
| Housing Height: |
| 1.547 inches |
| Housing Length: |
| 3.875 inches |
| Housing Width: |
| 1.781 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 2.344 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width: |
| 1.156 inches |
| Maximum Voltage Rating In Volts: |
| 600.0 ac and 240.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded hole |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, one position momentary single switch unit |
| Switch Release Force: |
| 4.5 inch-ounces |
| Switch Actuating Force: |
| 48.0 inch-ounces |
| Actuator Movement: |
| 10.0 pretravel degrees and 40.0 overtravel degrees and 4.0 differential degrees |
| Contact Load Current Rating At Maximum Rated Voltage: |

Terminal Type And Quantity:

4 screw

100.000 milliamperes resistive dc and 1.200 amperes resistive ac

NSN 5930-01-177-2329

Sensitive Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0