NSN 5930-01-177-2329

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-177-2329

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight and watertight
Overall Length:
3.875 inches
Overall Height:
1.547 inches
Overall Width:
2.250 inches
Case Material:
Metal
Housing Height:
1.547 inches
Housing Length:
3.875 inches
Housing Width:
1.781 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 two circuit, one position momentary single switch unit
Switch Release Force:
4.5 inch-ounces
Switch Actuating Force:
48.0 inch-ounces
Actuator Movement:
10.0 pretravel degrees and 40.0 overtravel degrees and 4.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:

Terminal Type And Quantity:

4 screw

100.000 milliamperes resistive dc and 1.200 amperes resistive ac

NSN 5930-01-177-2329

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0