Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-177-3773

| New Online at https://aeiobasegroup.com/nsi//3930-01-177-3773 |
|---|
| Overall Length: |
| 2.520 inches |
| Overall Height: |
| 1.780 inches |
| Overall Width: |
| 1.330 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.100 inches single mounting facility |
| Individual Section Quantity: |
| 3 |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.342 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 0.900 inches single mounting facility |
| Operating Tempurature Range: |
| -65.0/+85.0 degrees celsius |
| End Application: |
| Test set, airborne laser tracker an/aam-55 |
| Mounting Method: |
| Bracket single mounting facility and unthreaded hole single mounting facility |
| Actuator Type: |
| Thumbwheel all actuators |
| Features Provided: |
| Rfi shielding and dummy section |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 8 all actuators |
| Terminal Type: |
| Printed circuit |
| Contact Load Current Rating: |
| 125.0 milliamperes resistive load dc at sea level |
| Readout Indicator Marking: |
| 1, 2, 3, 4, 5, 6, 7, 8 each section |
| Contact Arrangement Truth Table: |
| Bcd, separate common to not-true bits, 2 pole - 8 positions each section |
| Color: |
| Red each lamp |
| Style Designator: |
| |

Rectangular inline indicating

Code Indicating Wheel Switch - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0