

View Online at <https://aerobasegroup.com/nsn/5930-01-177-4000>

Body Style:

Printed circuit

Hazardous Locations/environmental Protection:

Dustproof and vibration resistant and shock resistant

Overall Length:

Between 0.270 inches and 0.290 inches

Overall Height:

Between 0.578 inches and 0.628 inches

Overall Width:

Between 0.370 inches and 0.390 inches

Body Length:

Between 0.270 inches and 0.290 inches

Body Width:

Between 0.370 inches and 0.390 inches

Body Height:

Between 0.237 inches and 0.257 inches

Case Material:

Plastic

Switch Actuator Quantity:

2

Actuator Style:

Rectangular

Actuator Height:

Between 0.195 inches and 0.205 inches

Actuator Width:

0.070 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Inscription:

22 single actuator

Maximum Voltage Rating In Volts:

30.0 dc

End Application:

Integrated underwater surveillance systems, communications program for combat theater (tri-tac) 4781

Inclosure Type:

Fully enclosed

Mounting Method:

Printed circuit

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes resistive dc

Terminal Type And Quantity:

4 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0