

View Online at <https://aerobasegroup.com/nsn/5930-01-177-4682>

**Overall Length:**

6.656 inches

**Overall Diameter:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.438 inches single mounting facility

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.188 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 each section periphery

**Throw Quantity:**

3 each section periphery

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

600.0 ac at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Contact Load Current Rating:**

20.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contact, rotor, and terminal surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, panel mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0