

View Online at <https://aerobasegroup.com/nsn/5930-01-177-4682>

Overall Length:

6.656 inches

Overall Diameter:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.438 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section periphery

Throw Quantity:

3 each section periphery

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

600.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Contact Load Current Rating:

20.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact, rotor, and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, panel mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0