

View Online at <https://aerobasegroup.com/nsn/5930-01-177-8929>

Thread Class:

3a single pressure connection

Overall Length:

3.750 inches

Outside Diameter:

0.438 inches single connection

Body Length:

2.500 inches

Overall Diameter:

1.380 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.688 inches

Operating Temperature Rating:

Between 28.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Clamp

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

7500.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+1600.00/+3000.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

2250.00 actuation point pounds per square inch gage and 2000.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

5.0 dc at sea level first voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0