## NSN 5930-01-177-8936



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-177-8936 **Thread Class:** 2a **Body Style:** Bushing/hole mounted **Overall Length:** 2.578 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches **Overall Height:** 1.250 inches **Overall Width:** 0.641 inches **Bushing Length:** 0.406 inches **Body Length:** 1.820 inches **Body Width:** 0.641 inches **Body Height:** 0.640 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.150 inches **Actuator Style:** Round **Actuator Diameter:** 0.247 inches **Actuator Height:** 0.209 inches **Actuator Free Position Height:** 0.740 inches **Maximum Voltage Rating In Volts:** 250.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing

Thread Size: 0.375 inches

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally closed, momentary action single switch unit

## **NSN 5930-01-177-8936** Sensitive Switch - Page 2 of 2



Switch Release Force:
3.0 ounces
Switch Actuating Force:
20.0 ounces
Actuator Movement:
Between 0.050 pretravel inches and 0.100 overtravel inches and 0.010 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Thread Series Designator:
Unef
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0