

View Online at <https://aerobasegroup.com/nsn/5930-01-177-9532>

Thread Class:

2a single mounting facility

Thread Length:

0.290 inches single mounting facility

Overall Height:

1.060 inches

Overall Width:

1.060 inches

First Flat Length:

0.320 inches single actuator

Flat Height:

0.160 inches single actuator

Shaft Diameter:

0.249 inches single actuator

Shaft Length:

0.350 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 12: 00 o'clock

End Application:

3805-01-150-4814 loader scoop ty

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

1 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.438 inches single mounting facility

Contact Voltage Rating In Volts:

24.0 highest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Quick disconnect, male

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

18.0 amperes resistive load highest dc voltage rating at sea level

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0