

View Online at <https://aerobasegroup.com/nsn/5930-01-178-4083>

Hazardous Locations/environmental Protection:

Watertight and dustproof

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

20.00 pounds per square inch gage

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+1.00/+7.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Special Features:

6800 ohm resistor across terminals

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0