## NSN 5930-01-178-4284

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-178-4284

| D. I. O. I.   |
|---|
| Body Style:   |
| Hole mounted  |
| Hazardous Locations/environmental Protection:   |
| Watertight  |
| Overall Length:   |
| 7.125 inches  |
| Overall Height:   |
| 4.500 inches  |
| Overall Width:  |
| 3.312 inches  |
| Case Material:  |
| Metal   |
| Actuator Style:   |
| Round   |
| Actuator Diameter:  |
| 0.500 inches  |
| Actuator Height:  |
| 1.875 inches  |
| Housing Height:   |
| 3.312 inches  |
| Housing Length:   |
| 4.625 inches  |
| Housing Width:  |
| 6.188 inches  |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length:     |
| 3.500 inches  |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width:      |
| 4.875 inches  |
| Maximum Voltage Rating In Volts:  |
| 480.0 ac and 500.0 dc   |
| Inclosure Type:   |
| Fully enclosed  |
| Nonpile-up Contact Arrangement:   |
| 1 two circuit, double break/double make, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage:                                 |
| 100.000 milliamperes resistive dc and 10.000 amperes resistive ac                     |
| Terminal Type And Quantity:   |
| 4 screw   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

-

## NSN 5930-01-178-4284

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0