

View Online at <https://aerobasegroup.com/nsn/5930-01-178-4285>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

3.316 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Body Diameter:

1.000 inches

Bushing Length:

Between 0.627 inches and 0.687 inches

Body Length:

1.505 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 1.751 inches and 1.811 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

32.0 ounces

Switch Actuating Force:

Between 48.0 ounces and 96.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 24.000 amperes lamp dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0