NSN 5930-01-178-5230

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-178-5230

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.348 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Tempurature Range:

-57.0/+71.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

9 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

9 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

NSN 5930-01-178-5230

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 36.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 200.0 milliamperes resistive load dc at sea level **Precious Material And Location:** Contact and terminal surfaces gold **Precious Material:** Gold Style Designator: Snap or line **Thread Series Designator:** Unf single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A052b0