

View Online at <https://aerobasegroup.com/nsn/5930-01-178-8034>

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Hazardous Locations/environmental Protection:

Corrosion resistant and vibration resistant

Overall Length:

1.500 inches

Overall Height:

4.200 inches

Overall Width:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.210 inches

Longest Horizontal Distance Between Mounting Centers:

1.112 inches

Longest Vertical Distance Between Mounting Centers:

1.112 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 28.0 degrees fahrenheit and 130.0 degrees fahrenheit

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

600.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Sensing Element Burst Pressure:

1200.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load single voltage and 100.0 milliamperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

275.00 actuation point pounds per square inch gage and 225.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0