NSN 5930-01-178-8453

Sensitive Switch - Page 1 of 2

Body Style: Hole mounted Overall Length: 0.780 inches



View Online at https://aerobasegroup.com/nsn/5930-01-178-8453

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.380 inches
Overall Height:
0.540 inches
Overall Width:
0.250 inches
Body Length:
0.780 inches
Body Width:
0.250 inches
Body Height:
0.360 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.090 inches
Actuator Length:
0.375 inches
Actuator Style:
Leaf
Actuator Width:
0.160 inches
Actuator Free Position Height:
0.350 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
End Application:
4920-01-121-9954 evacuation and fill station
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
7.0 ounces

NSN 5930-01-178-8453

Sensitive Switch - Page 2 of 2



Actuator	Mov	em	ent
----------	-----	----	-----

Between 0.218 pretravel inches and 0.030 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0