

View Online at <https://aerobasegroup.com/nsn/5930-01-178-8737>

Thread Class:

2a all threaded stud

Thread Length:

0.187 inches all threaded stud

Overall Height:

0.825 inches

Body Height:

Between 0.350 inches and 0.395 inches

Overall Diameter:

Between 0.560 inches and 0.640 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Threaded stud

Thread Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

170.00 actuation point degrees fahrenheit and 140.00 deactuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Test Data Document:

81349-mils24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc all threaded stud

Specification Data:

81349-mils24236/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0