

View Online at <https://aerobasegroup.com/nsn/5930-01-179-0280>

Hazardous Locations/environmental Protection:

Corrosion resistant and fungus resistant

Overall Length:

3.200 inches

Overall Height:

2.090 inches

Overall Width:

1.920 inches

Unthreaded Mounting Hole Diameter:

0.140 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.940 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.350 inches single mounting facility

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Features Provided:

Rfi shielding

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

16 2nd actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

3.0 amperes resistive load ac at sea level

Readout Indicator Marking:

72, 128, 144, 256, 288, 512, 576, 1024, 1152, 2048, 2304 1st section

Contact Arrangement Truth Table:

Binary coded, 11 positions 1st section

Color:

Black each indicator background

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0