

View Online at <https://aerobasegroup.com/nsn/5930-01-179-3721>

Thread Class:

3a single pressure connection

Thread Length:

0.390 inches single pressure connection and 0.494 inches single pressure connection

Overall Length:

2.000 inches

Outside Diameter:

0.469 inches single connection

Body Length:

Between 1.506 inches and 1.610 inches

Overall Diameter:

0.880 inches

Pressure Switch Type:

Gage

Width Across Flats:

Between 0.720 inches and 0.840 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Line

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch gage

Thread Size:

0.469 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 2.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

45.00 actuation point pounds per square inch gage and 28.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A048b0