

View Online at <https://aerobasegroup.com/nsn/5930-01-179-7093>

Hazardous Locations/environmental Protection:

Watertight and dustproof

Overall Height:

10.812 inches

Overall Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

4.000 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Shortest Vertical Distance Between Mounting Centers:

1.062 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

5600.00 pounds per square inch gage

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+500.00/+5000.00 actuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point hex nut with scale

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Special Features:

Hand reset

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0