NSN 5930-01-179-7919

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-179-7919

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
4.031 inches
Overall Height:
8.176 inches
Overall Width:
3.750 inches
Body Height:
4.801 inches
Tempurature Sensing Element Type:
Immersion well
Mounting Method:
Immersion well
Features Provided:
Internally grounded
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Screw
Contact Load Current Rating:
Contact Load Current Rating: 3.0 amperes resistive load single voltage
-
3.0 amperes resistive load single voltage
3.0 amperes resistive load single voltage Contact Adjustability:
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range:
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type:
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw Contact Stimulus Rating:
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw Contact Stimulus Rating: 1.00 differential point degrees fahrenheit and 3.00 differential point degrees fahrenheit
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw Contact Stimulus Rating: 1.00 differential point degrees fahrenheit and 3.00 differential point degrees fahrenheit Contact Voltage Rating In Volts:
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw Contact Stimulus Rating: 1.00 differential point degrees fahrenheit and 3.00 differential point degrees fahrenheit Contact Voltage Rating In Volts: 450.0 ac at sea level single voltage
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw Contact Stimulus Rating: 1.00 differential point degrees fahrenheit and 3.00 differential point degrees fahrenheit Contact Voltage Rating In Volts: 450.0 ac at sea level single voltage Special Features:
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw Contact Stimulus Rating: 1.00 differential point degrees fahrenheit and 3.00 differential point degrees fahrenheit Contact Voltage Rating In Volts: 450.0 ac at sea level single voltage Special Features: Manual reset; 316 ss thermowell
Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw Contact Stimulus Rating: 1.00 differential point degrees fahrenheit and 3.00 differential point degrees fahrenheit Contact Voltage Rating In Volts: 450.0 ac at sea level single voltage Special Features: Manual reset; 316 ss thermowell Media For Which Designed:
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw Contact Stimulus Rating: 1.00 differential point degrees fahrenheit and 3.00 differential point degrees fahrenheit Contact Voltage Rating In Volts: 450.0 ac at sea level single voltage Special Features: Manual reset; 316 ss thermowell Media For Which Designed: Gas or liquid
3.0 amperes resistive load single voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +75.00/+200.00 actuation point degrees fahrenheit Contact Adjustment Type: External actuation point screw Contact Stimulus Rating: 1.00 differential point degrees fahrenheit and 3.00 differential point degrees fahrenheit Contact Voltage Rating In Volts: 450.0 ac at sea level single voltage Special Features: Manual reset; 316 ss thermowell Media For Which Designed: Gas or liquid Style Designator:

NSN 5930-01-179-7919

Thermostatic Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A048b0