

View Online at <https://aerobasegroup.com/nsn/5930-01-180-0408>

Thread Class:

2a single mounting facility

Thread Length:

0.187 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof and explosion proof and moisture proof

Overall Length:

1.984 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.547 inches single actuator

Overall Diameter:

1.370 inches

Nonturn Device Radius:

0.260 inches at 12: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Pin at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

28 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Pin

Switch Actuator Positioning Increment:

12.8 degrees single actuator

Contact Load Current Rating:

125.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0