NSN 5930-01-180-1350

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-180-1350 **Body Style:** Hole mounted **Overall Length:** 1.520 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.875 inches **Overall Height:** 1.022 inches **Overall Width:** 0.410 inches **Body Length:** 1.095 inches **Body Width:** 0.410 inches **Body Height:** 0.625 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.404 inches **Actuator Length:** 0.112 inches **Actuator Style:** Rectangular **Actuator Height:** 0.097 inches **Actuator Width:** 0.168 inches **Actuator Free Position Height:** 0.612 inches **Maximum Voltage Rating In Volts:** 250.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit

Switch Release Force: 4.0 ounces

Switch Actuating Force:

12.0 ounces

NSN 5930-01-180-1350

Sensitive Switch - Page 2 of 2



Δ	cti	ıato	r M	OV.	Δm	۵n	4
м	CIL	เลเบ	ועו זי	Uν	em	eп	L.

0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0