

View Online at https://aerobasegroup.com/nsn/5930-01-180-3382 Overall Length: 3.520 inches Overall Height: 1.740 inches Overall Width: 2.120 inches Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Unthreaded hole single mounting facility	NSN 5930-01-180-3382 Rotary Switch - Page 1 of 2	Aerol
Overall Height: 1.740 inches Overall Width: 2.120 inches Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	View Online at https://aerobasegroup.com/nsn/5930-01-180-3382	
Overall Height: 1.740 inches Overall Width: 2.120 inches Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Overall Length:	
1.740 inches Overall Width: 2.120 inches Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	3.520 inches	
Overall Width: 2.120 inches Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Overall Height:	
2.120 inches Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	1.740 inches	
Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Overall Width:	
0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	2.120 inches	
Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Shaft Diameter:	
0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	0.625 inches single actuator	
Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Shaft Length:	
0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	0.970 inches single actuator	
Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Unthreaded Mounting Hole Diameter:	
Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	0.189 inches single mounting facility	
Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Individual Section Quantity:	
1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	1	
Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Longest Horizontal Distance Between Mounting Centers:	
1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	1.620 inches single mounting facility	
Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Longest Vertical Distance Between Mounting Centers:	
Nonpile-up nonsymmetrical Mounting Method:	1.250 inches single mounting facility	
Mounting Method:	Switch Contact Basic Design:	
-	Nonpile-up nonsymmetrical	
Unthreaded hole single mounting facility	Mounting Method:	
	Unthreaded hole single mounting facility	

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

440.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes inductive load dc at sea level

Special Features:

Plate inscription main/aux

NSN 5930-01-180-3382

Rotary Switch - Page 2 of 2



Sty				

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0