

View Online at https://aerobasegroup.com/nsn/5930-01-180-3382  Overall Length: 3.520 inches  Overall Height: 1.740 inches  Overall Width: 2.120 inches  Shaft Diameter: 0.625 inches single actuator  Shaft Length: 0.970 inches single actuator  Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility  Individual Section Quantity: 1  Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:  Unthreaded hole single mounting facility	<b>NSN 5930-01-180-3382</b> Rotary Switch - Page 1 of 2	Aerol
Overall Height: 1.740 inches Overall Width: 2.120 inches Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	View Online at https://aerobasegroup.com/nsn/5930-01-180-3382	
Overall Height: 1.740 inches Overall Width: 2.120 inches Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Overall Length:	
1.740 inches  Overall Width: 2.120 inches  Shaft Diameter: 0.625 inches single actuator  Shaft Length: 0.970 inches single actuator  Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1  Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	3.520 inches	
Overall Width: 2.120 inches Shaft Diameter: 0.625 inches single actuator Shaft Length: 0.970 inches single actuator Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility Individual Section Quantity: 1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Overall Height:	
2.120 inches  Shaft Diameter:  0.625 inches single actuator  Shaft Length:  0.970 inches single actuator  Unthreaded Mounting Hole Diameter:  0.189 inches single mounting facility  Individual Section Quantity:  1  Longest Horizontal Distance Between Mounting Centers:  1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers:  1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	1.740 inches	
Shaft Diameter:  0.625 inches single actuator  Shaft Length:  0.970 inches single actuator  Unthreaded Mounting Hole Diameter:  0.189 inches single mounting facility  Individual Section Quantity:  1  Longest Horizontal Distance Between Mounting Centers:  1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers:  1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	Overall Width:	
0.625 inches single actuator  Shaft Length: 0.970 inches single actuator  Unthreaded Mounting Hole Diameter: 0.189 inches single mounting facility  Individual Section Quantity: 1  Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	2.120 inches	
Shaft Length:  0.970 inches single actuator  Unthreaded Mounting Hole Diameter:  0.189 inches single mounting facility  Individual Section Quantity:  1  Longest Horizontal Distance Between Mounting Centers:  1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers:  1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	Shaft Diameter:	
0.970 inches single actuator  Unthreaded Mounting Hole Diameter:  0.189 inches single mounting facility  Individual Section Quantity:  1  Longest Horizontal Distance Between Mounting Centers:  1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers:  1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	0.625 inches single actuator	
Unthreaded Mounting Hole Diameter:  0.189 inches single mounting facility Individual Section Quantity:  1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Shaft Length:	
0.189 inches single mounting facility  Individual Section Quantity:  1  Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	0.970 inches single actuator	
Individual Section Quantity:  1 Longest Horizontal Distance Between Mounting Centers: 1.620 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method:	Unthreaded Mounting Hole Diameter:	
Longest Horizontal Distance Between Mounting Centers:  1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers:  1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	0.189 inches single mounting facility	
Longest Horizontal Distance Between Mounting Centers:  1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers:  1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	Individual Section Quantity:	
1.620 inches single mounting facility  Longest Vertical Distance Between Mounting Centers: 1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	1	
Longest Vertical Distance Between Mounting Centers:  1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	Longest Horizontal Distance Between Mounting Centers:	
1.250 inches single mounting facility  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	1.620 inches single mounting facility	
Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:	Longest Vertical Distance Between Mounting Centers:	
Nonpile-up nonsymmetrical  Mounting Method:	1.250 inches single mounting facility	
Mounting Method:	Switch Contact Basic Design:	
-	Nonpile-up nonsymmetrical	
Unthreaded hole single mounting facility	Mounting Method:	
	Unthreaded hole single mounting facility	

#### **Features Provided:**

Actuator knob

## **Contact Voltage Rating In Volts:**

440.0 ac at sea level

## **Mounting Facility Pattern:**

Four position rectangular single mounting facility

#### **Switch Actuator Indexing Position Quantity:**

2 single actuator

## Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab w/screw

#### **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

## **Switch Actuator Stop Device Type:**

Fixed stop single actuator

#### **Contact Load Current Rating:**

10.0 amperes inductive load dc at sea level

#### **Special Features:**

Plate inscription main/aux

# NSN 5930-01-180-3382

Rotary Switch - Page 2 of 2



Sty				

Tap, square frame

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0