NSN 5930-01-180-4014

Rotary Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-180-4014 |
|--|
| Hazardous Locations/environmental Protection: |
| Watertight |
| Overall Length: |
| 3.520 inches |
| Overall Height: |
| 1.740 inches |
| Overall Width: |
| 2.120 inches |
| Shaft Diameter: |
| 0.625 inches single actuator |
| Unthreaded Mounting Hole Diameter: |
| 0.189 inches single mounting facility |
| Individual Section Quantity: |
| 1 |
| Longest Horizontal Distance Between Mounting Centers: |
| 1.620 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 1.250 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up nonsymmetrical |
| Mounting Method: |
| Unthreaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 440.0 ac at sea level |
| Switch Actuator Momentary Position: |
| Clockwise single actuator and counterclockwise single actuator |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 3 single actuator |
| Shaft Type: |
| Round single actuator |
| Terminal Type: |
| Tab w/screw |
| Switch Actuator Positioning Increment: |

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

NSN 5930-01-180-4014

Rotary Switch - Page 2 of 2



| • | | |
|-------|----------|-------|
| StVID | l Jacian | ator. |
| OLYIC | Design | atoi. |

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0