

View Online at <https://aerobasegroup.com/nsn/5930-01-180-4019>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

2.960 inches

Overall Height:

0.740 inches

Overall Width:

0.740 inches

Body Width:

0.740 inches

Body Height:

0.740 inches

Case Material:

Plastic

Actuator Length:

0.740 inches

Actuator Style:

Rectangular

Actuator Height:

0.300 inches

Actuator Width:

0.740 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.660 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

Precious Material And Location:

Terminal and bezel surfaces gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

11 pin

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0