NSN 5930-01-180-9898

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-180-9898

Thread Class:

2b single mounting facility

Overall Length:

4.934 inches

Overall Diameter:

3.750 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.300 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.300 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level30.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level10.0 amperes resistive load dc at sea level

Precious Material And Location:

Rotor and terminal surfaces silver

Precious Material:

Silver

NSN 5930-01-180-9898

Rotary Switch - Page 2 of 2

Style Designator:

Tap, circular frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

