

View Online at <https://aerobasegroup.com/nsn/5930-01-181-0054>

**Thread Class:**

2a single mounting facility

**Thread Length:**

6.50 millimeters single mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

66.4 millimeters

**Shaft Diameter:**

6.4 millimeters single actuator

**Shaft Length:**

16.0 millimeters single actuator

**Overall Diameter:**

52.6 millimeters

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 9: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Features Provided:**

Metallic inclosure

**Thread Size:**

0.438 inches single mounting facility

**Contact Voltage Rating In Volts:**

24.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flat, undercut single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level and 30.0 amperes inductive load dc at sea level

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0